


Brillia
COLLECTION

120x180 CM
GVT



EMOTIONS ON THE
S U R F A C E

COLLECTION 2024/25

FULL DIGITAL MATT THAT DEFINES SUBTLE SOPHISTICATION

A Full Digital Matt tiles finish exudes elegance and adds charm to any space. With its soft, velvety texture and anti-glare surface, Full Digital Matt tiles create a serene ambiance, adding depth and warmth to interiors. The non-reflective finish minimizes imperfections, ensuring a smooth, refined look. Embrace the quiet luxury of Full Digital Matt tiles finishes to transform your living area into a sanctuary of style and tranquility.

ENDURING TILES, CRAFTED IN INDIA



Rollence Granito is a leading manufacturer and exporter of high-quality vitrified ceramic tiles, trusted both locally and globally. Specializing in a wide range of products for residential, commercial, and government projects, we are committed to delivering excellence. Our team blends innovation with expertise to offer customizable ceramic and porcelain tiles, perfect for any space. With a strong focus on quality and design, Rollence ensures every tile reflects our dedication to craftsmanship, making us the top choice for your dream projects

BRAND PROMISE

QUALITY SERVICES
ETHICAL PRACTICE
VALUE AND MONEY
CUSTOMER DELIGHT



THICKNESS

15MM 9MM



THE PERFECT BLEND OF STYLE, STRENGTH, AND VERSATILITY

Features

-  Quality raw Materials
-  Easy to clean
-  No alteration in color
-  Non-absorbent
-  Resistant to frost
-  Resistant to liquids and acids
-  Versatile for any project
-  Resistant to scratches and abrasions
-  Resistant to thermal shock

Applications


-  Residences
-  Hotel
-  Shops
-  Restaurants
-  Airports
-  Malls
-  Railway Stations
-  interiors
-  Kitchens




ACIER BEIGE




ACIER BROWN



ACIER WHITE



BELGIAN GREY



CIENTO DOVE



CLOUD ONYX
WHITE



DORIAN BEIGE



DORIAN GRIS



INSPERIA BEIGE



LASA BLUE



LASA CREMA



LASA GREY



LASA IVORY



MARCO CHOCO



MARCO CREMA



MARCO GREY



MASETRATI SILK



MISTRAL GRIS



MISTRAL IVORY



MISTRAL SILK



MISTRAL SILVER



MORION GREY



MORION LIGHT
GREY



MORION TAUPE



STELLAR BEIGE



STELLAR LIGHT
GREY



Touch & Scan



ACIER BEIGE



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------



ROLLENCE
GRANITO

ACIER BEIGE

360°
Touch & Scan





ACIER BROWN



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------



ACIER BROWN





ACIER WHITE



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------



ACIER WHITE

360°
Touch & Scan





BELGIAN GREY



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------

BELGIAN GREY

360°
Touch & Scan





CIENTO DOVE




Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------





**CLOUD
ONYX WHITE**



Size: 120x180cm

Finish: **Digital Matt**

Thickness: 9mm

Random: 3






CLOUD ONYX WHITE

360°
Touch & Scan





DORIAN BEIGE



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	-----------------------------	-----------------------	------------------



DORIAN BEIGE

360°
Touch & Scan





DORIAN GRIS



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------



DORIAN GRIS

360°
Touch & Scan





INSPERIA BEIGE



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------

 **ROLLENCE**
GRANITO



INSPERIA BEIGE


Touch & Scan







LASA BLUE



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------



LASA BLUE

360°
Touch & Scan





LASA CREMA



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------

ROLLENCE
GRANITO

LASA CREMA

360°
Touch & Scan





LASA GREY



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------

LASA GREY

360°
Touch & Scan





LASA IVORY



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------





MARCO CHOCO



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------





MARCO CREMA




Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------





MARCO GREY



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------





MASETRATI SILK



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------





MISTRAL GRIS



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------




MISTRAL GRIS

360°
Touch & Scan






MISTRAL IVORY




Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------

 **ROLLENCE**
GRANITO



MISTRAL IVORY


Touch & Scan





MISTRAL SILK



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------



ROLLENCE
GRANITO

MISTRAL SILK

360°
Touch & Scan





MISTRAL SILVER



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------



MISTRAL SILVER

360°
Touch & Scan





**MORION LIGHT
GREY**



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------



MORION LIGHT GREY

360°
Touch & Scan





MORION TAUPE



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------



MORION TAUPE

360°
Touch & Scan





MORION GREY



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------





STELLAR BEIGE



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------



STELLAR BEIGE

360°
Touch & Scan





**STELLAR LIGHT
GREY**



Size: 120x180cm	Finish: Digital Matt	Thickness: 9mm	Random: 3
-----------------	----------------------	----------------	-----------

STELLAR LIGHT GREY

360°
Touch & Scan




TRANSPORTATION, HANDLING AND STORAGE OF SLAB

When transporting the slabs, they must be secured properly to avoid storage problems. If the tiles are transported over a short distance, the slabs should be kept vertically in the vehicle and at back side of slabs there should be proper packing or ply to avoid breakage. If the tiles are transported over a longer distance, they should be kept on an A shape frame, as shown in Fig A and B. With this method, we can avoid any breakage of slabs during transit.

Fig. A



Fig. B



MANUAL HANDLING OF SLAB

When handling slabs manually, the primary tool used is the regular suction cup (Fig. A and B). Using these, workers can shift the tiles easily.

Fig. A






Fig. B



The suction cups should be attached to the face of the tile, not its rear side. The instructions by the manufactures should always be followed.

Fig. C



If the surface of the slab is textured, the best way to handle the slabs manually is by using a Large Format Tile (LFTI) Carrier System (Fig. C) with suction cups that hold the tile from all four sides. By using this method, workers can lift or shift the tiles easily without any damage and will require the manpower of two people.





Fig. F

STORAGE

The slabs should be stored on A shape frame, made up of wood or steel with rubber lining, as shown below.

Fig. D



LAYING & FIXING

(A) The slabs are very heavy, large-sized, and have sharp edges. So, it is important for the people transporting the tiles to wear protective gear like gloves during transportation. We also recommend the use of double or triple suction cups for a firm grip of the tile while ensuring the safety of the operator. Before transporting the tile, it should be thoroughly cleaned to get rid of any dust or moisture and make sure that the grip of the tile is not compromised. Then the suction cups should be placed on the face of the tile and be checked for how well they are stuck to the surface before lifting the tile.

b) The following points should be considered while laying the slabs:

1. The subfloor or the laying surface should be prepared properly before laying the slabs. The laying surface should be rigid, non-flexing, and capable of supporting the expected load with minimal or no deflection.
2. A leveled subfloor is extremely important to keep the slabs from cracking.
3. Provision of proper curing for the subfloor, for around 24 to 48 hours before tiling work.

For internal or external application, it is essential to select the appropriate cement-based, fiber-reinforced or ready-mixed adhesive to ensure that the slabs are properly fixed.

Fig. G



Fig. H






Fig. I




4. Once the subfloor is clean and ready, the adhesive should be spread evenly covering the entire area using a 10x10mm square notch trowel (Fig. G). The adhesive should cover 5cm to 10cm more than the size of the slabs. The adhesive should always be applied in stripes running parallel with the short edge to remove any air pockets or bubbles.
5. The slabs require back-buttering due to their large format. Back-buttering means applying a layer of adhesive at the back of the tile using a trowel (Fig. I). The slabs should be fixed on a handing frame with the use of suction cups in a vertical position, as shown in Fig. C.
6. To apply adhesive on the laying surface, a 10x10mm square notch trowel should be used whereas a 5x5mm square notch trowel should be used for back-buttering.
7. After fixing the slabs on a handing frame with the use of suction cups in a vertical position, it should be lowered slowly into a horizontal position and firmly pressed into the adhesive along with a surface vibrator or a rubber mallet.
8. Use a levelling system to avoid lippage and give a smooth and even surface at every joint. Levelling systems are available from 1 mm to 10mm.
9. A closer system can be used to close the tiles nearer to each other and shift the tile slightly up and down at the time of fixing.
10. The backs of the slabs must be regularly checked to make sure that there is full contact between the adhesive and the tile surface. If a hollow sound is heard during fixing, the tile should be lifted again and provided with extra adhesive at that particular area to give proper strength to the tile.
11. After completing the tiling work, it is recommended to put a protection sheet on tiles until the completion of all civil work. It is recommended that the grouting work be done at the very last, after completing all civil work. We can use sanded grouts with hardener or epoxy grout, depending on the area of usage or as per instructions of the site in-charge.

TOOLS RECOMMENDED FOR SLABS


Notch trowel (5mm to 10mm)




Levelling system with plier



Tiles Closer System




Suction Cups



Tills Lifter



Adhesive mixture



Surface Vibrator



Rubber Mallet




Joint scrapper



TILE CUTTING

Mark the portion to be cut out from the ends of the slab using a pencil. Then, properly position the cutting guide with a cutting carriage so that the references on the guide coincide with the lines marked on the slab. Lock the cutting. Guide with the cutting carriage in place using the suction cups. It is vital to keep the pressure and movement of the cutting carriage constant along the whole length of the cut to ensure correct scoring.

Score one end of the slab by 15cm pushing the cutting carriage towards the edge of the slab. Complete the scoring up to the opposite end of the slab.



CLEANING

CLEANING AFTER LAYING

After laying the slabs on the floor or wall, it should be cleaned well to remove any residual grouting and the normal dirt acquired from building works.

A cementitious de-scaler can be used for cleaning the joints, as it is mildly acidic and does not emit harmful fumes, ensuring the safety of the user. In case of material laid with epoxy or resinous grouting, it is recommended to clean after laying with specific detergent or tile cleaner.



REGULAR MAINTENANCE

To clean the floor thoroughly, we recommend using a natural detergent with high cleaning power. In case of strong dirt that gets encrusted with time, we recommend consulting the following ways to find the perfect solution to every situation:

TYPE OF DIRT	PRODUCT
Cement, Metal tracer, rust	Cementitious descaler
Residuals, stains and halos of epoxy joints	Epoxy descaler
Grease, tire marks, colours, markers etc.	Non soap degrease
Graffiti	Acetone and anti-graffiti

RECOMMENDATIONS

Drying Process

Once the tiles have been grouted and the excess grout has been cleaned off, it is important to wait till the tiled surface is dried completely before cleaning. The recommended waiting time is 5 days, before cleaning or using the tiled surface.

Protecting from Liquid

The newly tiled surface must be protected from water and moisture while the adhesive and grouting materials are maturing and hardening. This is particularly important for outdoor spaces and areas, where there is a risk of freezing.

Damage Preventio

It is important to protect the newly tiled surface against mechanical or chemical damage resulting from subsequent work carried out by other professionals or due to later installations. Damage can be prevented by covering the floor tiles with thick cardboard or similar material.

Cleaning Products

For the final cleaning of the tiled surface, the products used should be compatible with the chemical resistance of the tiles. Avoid using solid detergents with abrasive particles and solutions containing hydrofluoric acid, which attacks the glaze and causes irreversible damage to the vitrified tile.



KAG.GRANITO.LLP

Sr. No. 197, Opp. Amardham Ashram , Matel Road,
Matel - 363 621 ,Tal. Wankaner, Dist. Morbi ,(Guj.)INDIA.
+91 9726055557 | info@rollence.in | www.rollence.in